



JŪRAS UN DARBA APĢĒRBS ▶ ЗАЩИТА ОТ ПАДЕНИЙ

CONNECTOR 31 – DIELECTRIC

Produkta kods: SH31E

- The 31 Dielectric Connector is engineered for marine and offshore professionals working in environments with electrical hazards. This connector serves as a critical link between various elements of a fall protection or restraining system, ensuring secure connections in demanding maritime settings.

Key Features:

- **Dielectric Strength:**
Provides electrical insulation with a dielectric strength of 27.2 kV/mm, suitable for tasks near live electrical components.
- **Automatic Locking Mechanism:**
Features an automatic threaded locking system that requires deliberate actions to open, preventing accidental disengagement.
- **Robust Construction:**
Manufactured from plastic-coated steel, offering excellent mechanical properties and resistance to harsh marine conditions.

Technical Specifications:

- Material: Plastic-coated steel
- Opening Diameter: 51 mm
- Weight: 580 g
- Breaking Strength: 23 kN
- Useful Life: 10 years from manufacturing date; 5 years from first use

- CE Certified
- EN 362:2004



Izmērs:

One

size
Krāsa:

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001:2015 =

