



JŪRAS UN DARBA APĢĒRBS ► ЗАЩИТА ОТ ПАДЕНИЯ

46 WEBBING LANYARD

Produkta kods: L46

- The 46 Webbing Lanyard is a robust and reliable component designed for fall arrest systems in marine and offshore environments. Constructed from high-strength polyester webbing, this lanyard ensures durability and safety during tasks performed at height.

Key Features:

- **Material:** 47 mm wide polyester webbing offering excellent tensile strength and resistance to abrasion.
- **Protective Covers:** Both terminations are equipped with polyester covers to protect the webbing from friction caused by connectors.
- **Minimum Breaking Load:** 22 kN, ensuring reliable performance under load conditions.
- **Length Options:** Available in lengths of 1 m, 1.5 m, and 2 m to suit various operational requirements.
- **Weight:** 0.140 kg, facilitating ease of handling without compromising strength.
- **Service Life:** Theoretical useful life of 15 years from the date of manufacture, providing long-term reliability.

Technical Specifications:

- **Material:** High-strength polyester webbing.
- **Width:** 47 mm.
- **Breaking Load:** 22 kN.
- **Available Lengths:** 1 m, 1.5 m, and 2 m.
- **Weight:** 0.140 kg.

- CE Certified
- EN 354:2002



Izmērs: One
size

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001:2015 =

